

Information Technical Specs

For use in: Offices, cubicles, Healthcare/ Medical facilities, Motels, Churches, Banks, Home

ASM-2600 Privacy Provider

Features

- Compact Masking System
- Analog Masking Source
- Light Weight & Portable
- Carry in brief case, purse
- Volume Control
- Low-pass Filter
- 12 Foot Power Cord
- 110-120 Volts: 50-60 Hertz

Size: 6" high, 4" wide, 1" thick



General Applications

The ASM-108 Privacy Provider emits a precisely enhanced analog signal that covers, or masks, Intelligible conversation and distractive outside noises within your business, healthcare, or home environment. There is a volume control and a low-pass filter that can be adjusted to meet your needs for loudness and tone. It is totally portable, weighs 10.2 ounces, and is warm gray in color.

The exact size measures 1 inch high by 3.75 inches wide by 6.35 inches long.

They plug into standard wall outlets (110-120 Volts) and units can be daisy chained to each other.

This UL listed unit comes with a 12 foot power cord and Velcro mounting strips (if needed).

General Description of Operation

The ASM108 Privacy Provider is designed for small in-room placement where a central masking system is not affordable or where unit is temporary or needs to be moved frequently.

The privacy provider can be used in **commercial environments** such as: secretarial areas, social service, human resources, CPA Firms, Law / financial offices, mortgage/ title companies, Doctor's Offices, Exam Rooms, Admitting, Patient Waiting Rooms, Out-Patient Surgeries, Psychotherapy, Dental Offices, churches, banks

In **residential areas** such as: home offices, multi-tenant apts, condos, dormitories, motels, hotels, and Bedrooms for Restless Sleepers who wake up easily, The uses are unlimited.

If you do not want to hear others; place the unit by you (the listener). If you do not want others to hear you; place the unit by them. Can also be placed in hallway, outside conferencing room door.

To Install: Use small screw driver to adjust **volume** and **tone**. Turn **Tone** knob almost ¼ turn clockwise (to the right). Turn volume knob to volume desired.

Placement: Conceal, position and/or Velcro unit under desk, behind file cabinet, under couch, under beds (in motels). When privacy levels are inadequate between two rooms, place a unit in each room.

Specifications: Noise source, Analog, Gaussian random, non-deterministic. **Electrical Power** Output@ 8 ohms = 0.5 Watts avg.
Power requirements: 13 to 18 VDC@220 mA max. **Low-pass filter** 6db / octave

Distributed by:

American Sound Masking - Florida Sound Masking

1215 Polaris Parkway, Suite 274 - Columbus, Ohio 43235

Phone: 800-766-8959 - Fax: 877-577-5448